

DAT Tape Drives

Best-value tape solution for SMBs

DAT is the most successful tape backup technology of all time with more than 16 million DAT drives shipped, and with a current world-wide installed base of over 6 million drives.

DAT tape technology continues to meet the needs of the small and medium-sized business (SMB) market providing a reliable and low-cost tape backup solution. DAT remains the first choice for SMBs looking to protect low-end servers. Tandberg Data DAT tape drives are available with a range of capacities (72GB, 160GB and 320GB) and a choice of interfaces SCSI, SAS and USB.

Tandberg Data DAT tape drives are easy to use and easy to install, customers can benefit from out of the box to backup in less than 60 seconds. Tandberg Data DAT family provides a balance of price and performance offering up to 320GB of compressed data on a single cartridge at speeds of up to 86.4GB/hr*.

Tandberg Data offers a range of DAT models including internal, external and rackmount configurations. The low cost of ownership is provided through low-cost, durable DAT media. The two generation backward compatibility provides a seamless upgrade path from older DAT drives. Tandberg Data DAT products are extensively tested to ensure they are fully compatible with a wide range of servers, operating systems and backup software. Tandberg Data DAT tape drives are supplied with a 3-year warranty.

Protect your small or medium-sized business, remote office or workgroup with a Tandberg Data DAT tape drive.



Key Benefits

- Best Value Tape**
 Low hardware and media cost combine to make DAT the best value tape solution
- Performance**
 Up to 86.4GB/hr*
- Ease of Use**
 Out of box to backup in less than 60 seconds
- Future Proof**
 8-generation roadmap, capacities up to 320GB*
- Reliability**
 Proven reliability MTBF of 125,000 hrs at 100% duty cycle
- Low Power**
 DAT320 has the lowest power consumption of any tape drive on the market.
- Security**
 Protect your data with AES 256-bit Encryption (DAT320 only)
- Leading Service & Support**
 3-year warranty and 1-year Advanced Replacement Service** (Free technical support)

* Assumes a 2:1 compression ratio

** Availability dependent on location



DAT tape drives offer up to 320GB of compressed data on a single cartridge at compressed speeds of up to 86.4GB/hr.

Specifications

	Tandberg DAT72	Tandberg DAT160	Tandberg DAT320
Recording Method	4 mm Helical Scan	8 mm Helical Scan	8 mm Helical Scan
Capacity (native/compr.)	36GB / 72GB*	80GB / 160GB*	160GB / 320GB*
Transfer Rate (native/compr.)	3.2MB/s / 6.4MB/s*	6.9MB/s / 13.8MB/s*	12MB/s / 24MB/s*
Data Access Time	68 sec.	50 sec.	50 sec.
Average Load/Unload Time	15 sec.	35 sec.	45 sec.
Rewind Time (end to end)	120 sec.	92 sec.	120 sec.
Recommended Media	DAT72 (170m)	DAT160 (150m)	DAT320 (150m)
Backward Read/Write Compatibility	DDS3 and DDS4	DDS4 and DAT72	DAT160
Data Compression	Lempel-Ziv (DCLZ)	Lempel-Ziv (DCLZ)	Lempel-Ziv (DCLZ)
WORM Compatible	No	Yes	Yes
Encryption Compatible	No	No	Yes
Interface Type	SCSI-3 Ultra 160 LVD USB 2.0	SCSI-3 Ultra 160 LVD USB 2.0	SAS 1.1 USB 2.0
Interface Connector SCSI	68-pin HD (internal) 68-pin HD (external)	68-pin HD (internal) 68-pin HD (external)	N/A
Interface Connector USB	Std B-type (internal) Std A-type (external)	Std B-type (internal) Std A-type (external)	Std B-type (internal) Std A-type (external)
Interface Connector SAS	N/A	N/A	SAS SFF8482 (internal)
MTBF Hours	125,000 hours @ 100% duty cycle	125,000 hours @ 100% duty cycle	125,000 hours @ 100% duty cycle

Environmental Specifications

Temperature (operating)	5C to 40C (41F to 104F)	5C to 40C (41F to 104F)	5C to 40C (41F to 104F)
Temperature (non-operating)	-40C to 70C (-40F to 158F)	-40C to 70C (-40F to 158F)	-40C to 70C (-40F to 158F)
Relative Humidity (operating)	20 to 80% (non-condensing)	20 to 80% (non-condensing)	20 to 80% (non-condensing)
Relative Humidity (non-operating)	5% to 95% (non-condensing)	5% to 95% (non-condensing)	5% to 95% (non-condensing)

Power Requirements

Internal	+5V ± 5% (100mV Max ripple) @0.8A +12V ± 10% (150mV Max ripple) @0.3A	+5V ± 5% (100mV Max ripple) @1.1A +12V ± 10% (150mV Max ripple) @0.4A	+5V ± 5% (100mV Max ripple) @0.78A +12V ± 10% (150mV Max ripple) @0.3A
External	100 to 240 VAC, 50-60 Hz, auto-ranging	100 to 240 VAC, 50-60 Hz, auto-ranging	100 to 240 VAC, 50-60 Hz, auto-ranging
Power Consumption (average)	7.1 W	10.3 W	6.1 W
Certification	CSA Certification to C22.2, No. 60950 (cCSAus), TUV EN60950 (IEC 60950), FCC and CE Declaration of Conformity, FCC 47 CFR Parts 15, NOM, VCCI. C-TICK, RRL, BSMI, GOSH Approved (AS/NZS CISPR22)		
Warranty	3-year warranty and 1-year Advanced Replacement Service**		

* Assumes a 2:1 compression ratio

** Availability dependent on location

About Tandberg Data

Tandberg Data is a leading global supplier of data protection solutions. Tandberg Data offers a wide selection of secondary storage solutions, ranging from disk-based solutions, such as the RDX® QuikStor™ and the Tandberg DPS1000 Series, to automated tape solutions like the StorageLoader and StorageLibrary Series. Tandberg Data also offers tape drives, based on the LTO™, SLR™, and VXA® tape technology platforms, and media. Tandberg Data solutions are supported by robust, easy to use software, such as RDX® FileKeeper™, the continuous data protection solution for the RDX QuikStor. All solutions are supported through a worldwide service and support network, recognised globally for its outstanding levels of service. Tandberg Data solutions are designed to meet the growing storage requirements of small and medium sized organizations with scalability, reliability, and backward compatibility features that ensure cost effective operation and long-term investment protection.

Tandberg Data GmbH
Feldstrasse 81
44141 Dortmund
Germany
Tel: +49 (0) 231 5436 - 0
Fax: +49 (0) 231 5436 - 111

Tandberg Data GmbH
Bloxham Mill Business Centre
Barford Road, Bloxham
Banbury, England, OX15 4FF
Tel: +44 (0) 845 070 6916
Fax: +44 (0) 1295 722 109

Tandberg Data S.A.S.
Multi Management Service
55 rue de l'Université
75007 Paris, France
Téléphone: 00 800 826 323 74
Télécopie: +33 (0)1 34 65 02 89

Tandberg Data Corporation
2108 55th Street
Boulder, CO 80301
USA
Tel: 303.442.4333
Fax: 303.417.7170

Tandberg Data (Asia) Pte. Ltd
7 Tai Seng Drive
#02-00
Singapore 535218
Tel: +65 (0) 6593 4700
Fax: +65 (0) 6281 7358